

K3-B

STANDALONE, CONVERTIBLE INTEGRATED READER
AND ACCESS CONTROL WITH BACKLIT KEYPAD



MAIN FEATURES

- > Backlit keypad, durable matte technic.
- > Multi-function, operating as access control or card reader, suitable for various occasions.
- > The unit accepts up to 500 users, allow entry via a 4-6 digits PIN and / or by presenting a proximity EM card.
- > Easy wiring of lock

SPECIFICATIONS

Operating voltage range	DC12-24V
Static input current	≤ 20mA
Max proximity card read range	5-8cm
Excitation Frequency	125KHz
Card transmit format	Wiegand 26
Keypad transmit format	4-6 digits key press to output card number format. Each press outputs a 4 bits or 8 bits data.
Size (Height × Width × Depth)	90 × 60 × 27mm
Operating temperature range	-40~60 ° C

Operating voltage range	DC12-24V
Static input current	≤ 20mA
Max proximity card read range	5-8cm
Excitation Frequency	125KHz
Card transmit format	Wiegand 26
Keypad transmit format	4-6 digits key press to output card number format. Each press outputs a 4 bits or 8 bits data.
Size (Height × Width × Depth)	90 × 60 × 27mm
Operating temperature range	-40~60 ° C